



DATASHEET

Gaming Spoon Microphone

SPECIFICATION	PARAMETERS
Voice Microphone	Unidirectional
Noise Microphone	Omnidirectional
Operating Voltage	2 – 10 Vdc
Maximum Current Consumption @ 5V	0.001mA
Output Impedance	2.2 k Ω
Frequency	20 – 20,000 kHz
Signal to Noise Ratio	81 dB SNR
Total Harmonic Distortion	0.0038% THD
Operating Temperature	-20 – 70 °C
Dimensions	
Weight	16g
Boom Length	160mm
Spoon Microphone LxWxD	37 x 20 x 13mm



DATASHEET

AFA ELM-01

SPECIFICATION	PARAMETERS
Voice Microphone	Unidirectional
Noise Microphone	Omnidirectional
Operating Voltage	2 – 10 Vdc
Maximum Current Consumption @ 5V	0.001mA
Output Impedance	2.2 kΩ
Frequency	20 – 20,000 kHz
Signal to Noise Ratio	81 dB SNR
Total Harmonic Distortion	0.0038% THD
Operating Temperature	-20 – 70 °C
Dimensions	
Weight	TBC
AFA ELM-01 LxWxD	TBC



DATASHEET

AFA ELM-02

SPECIFICATION	PARAMETERS
Voice Microphone	Unidirectional
Noise Microphone	Omnidirectional
Operating Voltage	2 – 10 Vdc
Maximum Current Consumption @ 5V	0.001mA
Output Impedance	2.2 kΩ
Frequency	20 – 20,000 kHz
Signal to Noise Ratio	81 dB SNR
Total Harmonic Distortion	0.0038% THD
Operating Temperature	-20 – 70 °C
Dimensions	
Weight	TBC
AFA ELM-02 LxWxD	TBC



DATASHEET

AFA ELM-03

SPECIFICATION	PARAMETERS
Voice Microphone	Unidirectional
Noise Microphone	Omnidirectional
Operating Voltage	2 – 10 Vdc
Maximum Current Consumption @ 5V	0.001mA
Output Impedance	2.2 kΩ
Frequency	20 – 20,000 kHz
Signal to Noise Ratio	81 dB SNR
Total Harmonic Distortion	0.0038% THD
Operating Temperature	-20 – 70 °C
Dimensions	
Weight	TBC
AFA ELM-03 LxWxD	TBC